

Product Details

5750 Sediment Interceptor

Technical Data



Dimensions:

390 square overall size

430 - Overall Height

- depth body flange to outlet center line

Connection - female 2" BSP threaded connection (50mm)

Materials - Tank - stainless steel; Bag - polyester

Weight - 18 kg

General Description:

Stainless Steel Sediment Interceptor (Solid material is captured in a filter bag - which needs to be lifted out of the interceptor for emptying at an appropriate frequency. Max. Flow Rate = 0.4 l/s), with 2" BSP dia. horizontal outlet. Sediment Interceptors are used to help prevent blockages where solids such as food scraps, hair, plaster, sediment etc. are discharged into drain lines. Note : Minimum clearance above cover of 450mm is required for removal of bucket / bag.

Materials:

Stainless Steel - Austenitic Grade 304 (Grade 316 optional on most products): Used for bodies, gratings, funnels, access covers, filter buckets and fixings. A corrosion-resistant metal containing significant amounts of nickel and chromium; AISI grade 304 stainless steel is used as standard, which is suitable for general use in and around buildings including most coastal locations. In applications such as swimming pools or having an aggressive atmosphere, grade 316 is recommended and is available optionally (if available, code 'M' will be listed under 'Options'). An even higher grade may be required for applications in highly corrosive environments including where exposure to seawater may be anticipated. Clean with soap and warm water rinse and wipe dry. Gratings may also be cleaned in certain dishwashers. Under no circumstances treat with metal scouring pads, metal scrapers or wire wool as these will contaminate surfaces leaving rust spots. Take care to cover stainless steel items when site work is going on, to avoid contamination with rust-inducing particles such as when mild steel or cast iron items are being cut.

All dimensions are in millimetres unless stated. In line with general practice all dimensions shown are nominal.

Wade International

Third Avenue, Halstead, Essex, CO9 2SX.

Telephone: +44 (0)1787 475151

Fax: +44 (0)1787 475579

e-mail: wadetech@alumascwms.co.uk

website: <https://www.alumascwms.co.uk/brands/wade/>

Dimensioned Section for 5750:

