


Note:
 WB224 Illustrated.
 Applicable to WB2 and WB3
 series assemblies.

1. Where applicable, screw spigot into body, using a suitable sealant to ensure the joint is watertight.
2. Position Body in roof deck and ensure that the outlet is accessible for pipework connection.
3. Install body such that flange is flush or sub-flush with roof deck. Ensure that body is fixed securely, either bonded or clamped to the deck if not cast in. NOTE: Membrane flange level is determined by roof build-up.
4. Refer to membrane manufacturer's instructions and prepare flange with suitable primer. Apply membrane, dressing over flange sufficiently into sump of body to enable it to be clamped. Position membrane clamping collar and secure to body using appropriate supplied fixings, see below.
 For membranes up to 15mm thick - use M8 x 30 countersunk head screws (Wade Pt No 50902055)
 For membranes over 15mm thick - use M8 x 50 countersunk head screws (Wade Pt No 50902059)
5. Fit grating to membrane clamping collar.
6. Fit optional gravel guard, if specified.

See also the general installation guidelines in Wade 'Roof Outlets' Brochure.

© 2011

ISS. No.	3		DRAWN	DC	16-2-11	TITLE		
C.N. No.			CHECKED			GENERAL INSTALLATION DETAIL FOR WB2 AND WB3 SERIES ROOF OUTLETS		
DATE	16-10-14		APPRVD.					
		Part Number				SCALE	DRG. No.	ISSUE No.
		50910000				NTS	INSTAL 44	3

WADE INTERNATIONAL LTD., THIRD AVENUE, HALSTEAD, ESSEX, CO9 2SX.

TEL: 01787 475151 FAX: 01787 475579

e-mail: tech@wade.eu web site: www.wade.eu